NSN 5905-01-211-2611

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-211-2611 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established liilength: 1.870 inches **Body Diameter:** 0.655 inches **Shaft Diameter:** 0.089 inches **Shaft Length:** 0.300 inches **Mounting Bushing Length:** 0.400 inches **Body Length:** 1.170 inches liidiameter: 0.655 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Fragility Factor:** Moderately rugged **Screw Thread Diameter:** 0.468 inches **Screw Thread Series Designator:** Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end **Mounting Method:** Standard bushing **Cubic Measure:** 0.502 cubic inches

Electrical Resistance Per Section:

406.0 ohms all sections

NSN 5905-01-211-2611

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 all sections
Power Dissipation Rating Per Section In Watts:
0.1 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 all sections
Special Features:
Radial operated shaft
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No