

View Online at <https://aerobasegroup.com/nsn/5905-01-211-2611>

**Section Quantity:**

4

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**liilength:**

1.870 inches

**Body Diameter:**

0.655 inches

**Shaft Diameter:**

0.089 inches

**Shaft Length:**

0.300 inches

**Mounting Bushing Length:**

0.400 inches

**Body Length:**

1.170 inches

**liidiameter:**

0.655 inches

**Shaft Style:**

Round

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Single shaft

**Fragility Factor:**

Moderately rugged

**Screw Thread Diameter:**

0.468 inches

**Screw Thread Series Designator:**

Uns

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Cubic Measure:**

0.502 cubic inches

**Electrical Resistance Per Section:**

406.0 ohms all sections

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

0.1 free air all sections

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 all sections

**Special Features:**

Radial operated shaft

**Terminal Type And Quantity:**

8 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A002a0