NSN 5905-01-211-2696

Film Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-211-2696

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: -50.0/+50.0/ Electrical Resistance: 8.450 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
8.450 kilohms Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Resistance Tolerance In Percent: -1.000/+1.000 Ambient Tempurature In Deg Celsius At Full Rated Power: -55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: -55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Full Rated Power: -55.0 Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: 175.0 Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Tempurature Range Of Tempurature Coefficient In Deg Celsius: -55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
-55.0/+175.0 Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Inclosure Method: Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Encapsulated Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Terminal Type: Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Wire lead Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Reliability Indicator: Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Not established Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Terminal Length: 1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
1.370 inches Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Body Diameter: 0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
0.100 inches Body Length: 0.341 inches Power Dissipation Rating In Watts:
Body Length: 0.341 inches Power Dissipation Rating In Watts:
0.341 inches Power Dissipation Rating In Watts:
Power Dissipation Rating In Watts:
0.100 free air
Style Designator:
Axial terminal each end
Test Data Document:
18876-10181751 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A001a0