Precision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-212-0040

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.780 inches

Undercut Width:

0.0570 inches

Body Diameter:

0.906 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

1.880 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

3600.0

Maximum Starting Torque:

1.00 inch-ounces

Maximum Running Torque:

0.80 inch-ounces

Maximum Stop Torque:

48.00 inch-ounces

Shaft End Play:

0.00500 inches

NSN 5905-01-212-0040

Precision Nonwire Wound Variable Resistor - Page 2 of 3



Shaft Runout: 0.001 inches Lateral Runout: 0.001 inches **Pilot Diameter Runout:** 0.00100 inches **Shaft Radial Play:** 0.001 inches Mechanical Backlash In Deg Angular Rotation: 1.0 **Fragility Factor:** Moderately rugged **Terminal Location:** Longitudinally positioned on the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 5.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 3600.0 **Function Conformity Tolerance Per Section:** -0.10 to 0.10 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section **Power Dissipation Rating Per Section In Watts:** 2.5 free air single section **Function Conformity Per Section:** Single section independent linearity **Resistance Tolerance Per Section In Percent:** -5.0 to 5.0 single section **Actuator Travel Control Feature:** Stops **Criticality Code Justification:** Feat **Function Characteristic Per Section:** Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Special Features:** Item must comply with requirements of defense electronics supply center production standard no. L03442 for navy nuclear propulsion plant products only **Terminal Type And Quantity:**

3 turret

NSN 5905-01-212-0040

Precision Nonwire Wound Variable Resistor - Page 3 of 3



Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0