NSN 5905-01-212-0041

Hybrid Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-212-0041

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
0.6250 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.781 inches
Undercut Width:
0.0620 inches
Body Diameter:
0.875 inches
Shaft Diameter:
0.1245 inches
Shaft Length:
0.375 inches
Body Length:
1.570 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round
Shaft Bearing Type:
Ball
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
3600.0
Maximum Starting Torque:
0.50 inch-ounces
Maximum Running Torque:
0.50 inch-ounces
Maximum Stop Torque:
128.00 inch-ounces
Shaft End Play:

0.005 inches

NSN 5905-01-212-0041

Hybrid Variable Resistor - Page 2 of 3



Shaft Runout:
0.001 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.0015 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
0.305 cubic inches
Electrical Resistance Per Section:
10.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.25 to 0.25 single section
-0.25 to 0.25 single section Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
•
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature: Stops
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: -70.0 to 70.0 single section Power Dissipation Rating Per Section In Watts: 2.5 free air single section Function Conformity Per Section: Single section independent linearity Resistance Tolerance Per Section In Percent: -5.0 to 5.0 single section Actuator Travel Control Feature: Stops Function Characteristic Per Section: Single section linear Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section Terminal Type And Quantity:

NSN 5905-01-212-0041

Hybrid Variable Resistor - Page 3 of 3



			ure:	

--

Demilitarization:

No

Fiig:

A002a0