## NSN 5905-01-212-7733

Wirewound Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-212-7733   |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
| -10.0 to 10.0 first temp coefficient                            |
| Electrical Resistance:  |
| 75.000 kilohms 3rd intermediate resistance value                |
| Resistance Tolerance In Percent:                                |
| -0.100 to 0.100 each resistor                                   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:         |
| 70.0  |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 125.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:    |
| -55.0 to 125.0 temp range of first temp coefficient             |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Quantity:  |
| 8   |
| Terminal Type:  |
| Pin   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.300 inches  |
| Body Length:  |
| 1.500 inches  |
| Body Width:   |
| 0.312 inches  |
| Body Height:  |
| 0.330 inches  |
| Schematic Diagram Designator:                                   |
| Series network  |
| Power Dissipation Rating In Watts:                              |
| 0.100 each resistor   |
| Identical Value Resistor Quantity:                              |
| 2 2nd intermediate resistance value                             |
| Style Designator:   |
| Single inline   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |

No

Demilitarization:

## NSN 5905-01-212-7733

Wirewound Fixed Resistor Network - Page 2 of 2



Fiig:

A001a0