

View Online at <https://aerobasegroup.com/nsn/5905-01-216-2015>

Section Quantity:

1

Body Style:

Cylindrical

Reliability Indicator:

Not established

Shaft Bearing Type:

Bearing

Actuator Type:

Recessed drive with slot

Effective Electrical Rotation In Deg Angular Rotation:

Between 190.0 and 210.0

Maximum Starting Torque:

300.00 centimeter-grams

Maximum Running Torque:

300.00 centimeter-grams

Maximum Stop Torque:

800.00 centimeter-grams

Fragility Factor:

Moderately rugged

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Features Provided:

Humidity proof

Electrical Resistance Per Section:

100.0 kilohms single section

Rotary Actuator Travel In Angular Deg:

Between 190.0 and 210.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-25.0 to 25.0 single section

Actuator Travel Control Feature:

Clutch

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0