NSN 5905-01-216-2149

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-216-2149 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Established **Reliability Failure Rate Level In Percent:** 0.010 **Mounting Hole Diameter:** 0.072 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.080 inches **Body Length:** 0.375 inches **Body Width:** 0.150 inches **Body Height:** 0.375 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** Between 5400.0 and 10800.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Fragility Factor:** Moderately delicate **Lateral Distance Between Mounting Hole Centers: Mounting Facility Quantity:**

0.419 inches **Terminal Location:** Rear end **Mounting Method:** Unthreaded hole **Cubic Measure:** 0.021 cubic inches

NSN 5905-01-216-2149

Fiig: A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
Between 5400.0 and 10800.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0 to 100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Clutch
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
85.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-39035 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 wire lead
Specification Data:
81349-mil-r-39035/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No