

View Online at <https://aerobasegroup.com/nsn/5905-01-216-6493>

Section Quantity:

1

Body Style:

Rectangular w/bushing

Reliability Indicator:

Not established

Overall Length:

20.0 millimeters

Overall Height:

22.5 millimeters

Shaft Diameter:

3.0 millimeters

Shaft Length:

10.0 millimeters

Mounting Bushing Length:

6.0 millimeters

Body Length:

10.0 millimeters

Body Width:

16.5 millimeters

Body Height:

17.5 millimeters

Shaft Style:

Round, slotted

Shaft Bearing Type:

Sleeve

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

260.0

Maximum Starting Torque:

250.00 inch-ounces

Maximum Running Torque:

250.00 inch-ounces

End Application:

6625-01-146-5801

Screw Thread Diameter:

6.0 millimeters

Screw Thread Series Designator:

Iso m

Terminal Location:

Lower adjacent side single row

Mounting Method:

Standard bushing

Cubic Measure:

2.8875 cubic centimeters

Electrical Resistance Per Section:

10.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

260.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

175.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-10.0 to 10.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

120.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0