

View Online at <https://aerobasegroup.com/nsn/5905-01-217-0599>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

3.7 millimeters

Body Length:

6.3 millimeters

Body Width:

8.9 millimeters

Body Height:

9.53 millimeters

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

200.0

Maximum Starting Torque:

300.00 centimeter-grams

Maximum Running Torque:

300.00 centimeter-grams

Center To Center Distance Between Terminals:

5.1 millimeters

Fragility Factor:

Moderately rugged

End Application:

6625-01-146-5801

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

2.54 millimeters

Electrical Resistance Per Section:

20.000 kilohms single section

Rotary Actuator Travel In Angular Deg:

200.0

Center To Center Distance Between Center Terminal And Outside Terminal:

2.54 millimeters

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-25.0 to 25.0 single section

Power Dissipation Rating Per Section In Watts:

0.3 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0