

View Online at <https://aerobasegroup.com/nsn/5905-01-217-1546>

Section Quantity:

1

Body Style:

Rectangular

Reliability Indicator:

Not established

Terminal Length:

0.180 inches

Body Length:

0.250 inches

Body Width:

0.400 inches

Body Height:

0.440 inches

Actuator Type:

Flush drive with slot-hole

Effective Electrical Rotation In Deg Angular Rotation:

262.0

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

End Application:

An/usm-488

Terminal Location:

Lower adjacent side two rows

Mounting Method:

Terminal

Center To Center Distance Between Terminal Rows:

0.100 inches

Cubic Measure:

0.044 cubic inches

Electrical Resistance Per Section:

2.000 megohms single section

Rotary Actuator Travel In Angular Deg:

262.0

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-100.0 to 100.0 single section

Power Dissipation Rating Per Section In Watts:

0.5 free air single section

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 single section

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Standard Taper Curve Per Section:

A single section

Terminal Type And Quantity:

3 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0