Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-217-1623

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-100.0 to 100.0 first temp coefficient

#### **Electrical Resistance:**

190.000 ohms highest resistance value

# **Resistance Tolerance In Percent:**

-2.000 to 2.000 each resistor

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 25.0

#### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

# Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 150.0 temp range of first temp coefficient

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

10

# Terminal Type:

Pin

# Reliability Indicator:

Not established

#### **Terminal Length:**

0.135 inches

#### **Body Length:**

0.990 inches

#### **Body Width:**

0.090 inches

#### **Body Height:**

0.195 inches

#### Schematic Diagram Designator:

Ladder network

#### **Power Dissipation Rating In Watts:**

1.700 total network

#### **End Application:**

F16a aircraft

#### Identical Value Resistor Quantity:

8 lowest resistance value

#### Special Features:

Burn in required

#### Style Designator:

Single inline

#### **Test Data Document:**

12436-6010292 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# NSN 5905-01-217-1623

Film Fixed Resistor Network - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0