

View Online at <https://aerobasegroup.com/nsn/5905-01-217-8510>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Overall Length:**

46.0 millimeters

**Body Diameter:**

17.0 millimeters

**Shaft Diameter:**

6.0 millimeters

**Shaft Length:**

30.0 millimeters

**Mounting Bushing Length:**

10.0 millimeters

**Body Length:**

16.0 millimeters

**Overall Diameter:**

27.0 millimeters

**Undercut Diameter:**

3.2 millimeters

**Shaft Style:**

Round, stepped

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Dual concentric

**Effective Electrical Rotation In Deg Angular Rotation:**

300.0

**Nonturn Device Location:**

At 9 oclock

**Nonturn Device Radius:**

7.5 millimeters

**End Application:**

6625-01-146-5801

**Undercut Length:**

10.0 millimeters

**Screw Thread Diameter:**

1.25 millimeters

**Screw Thread Series Designator:**

Iso m

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

10.000 kilohms all sections

**Rotary Actuator Travel In Angular Deg:**

300.0

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

150.0 all sections

**Power Dissipation Rating Per Section In Watts:**

0.125 free air all sections

**Resistance Tolerance Per Section In Percent:**

-20.0 to 20.0 all sections

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

50.0 all sections

**Standard Taper Curve Per Section:**

A all sections

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0