

View Online at <https://aerobasegroup.com/nsn/5905-01-217-8510>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Overall Length:

46.0 millimeters

Body Diameter:

17.0 millimeters

Shaft Diameter:

6.0 millimeters

Shaft Length:

30.0 millimeters

Mounting Bushing Length:

10.0 millimeters

Body Length:

16.0 millimeters

Overall Diameter:

27.0 millimeters

Undercut Diameter:

3.2 millimeters

Shaft Style:

Round, stepped

Shaft Bearing Type:

Sleeve

Actuator Type:

Dual concentric

Effective Electrical Rotation In Deg Angular Rotation:

300.0

Nonturn Device Location:

At 9 oclock

Nonturn Device Radius:

7.5 millimeters

End Application:

6625-01-146-5801

Undercut Length:

10.0 millimeters

Screw Thread Diameter:

1.25 millimeters

Screw Thread Series Designator:

Iso m

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Electrical Resistance Per Section:

10.000 kilohms all sections

Rotary Actuator Travel In Angular Deg:

300.0

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

150.0 all sections

Power Dissipation Rating Per Section In Watts:

0.125 free air all sections

Resistance Tolerance Per Section In Percent:

-20.0 to 20.0 all sections

Actuator Travel Control Feature:

Stops

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

50.0 all sections

Standard Taper Curve Per Section:

A all sections

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A002a0