NSN 5905-01-217-8513

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-217-8513

Section Quantity:
1
Body Style:
Rectangular
Reliability Indicator:
Not established
Body Length:
10.0 millimeters
Body Width:
16.5 millimeters
Body Height:
11.5 millimeters
Actuator Type:
Flush drive with slot-hole
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
50.00 centimeter-grams
Maximum Running Torque:
50.00 centimeter-grams
End Application:
6625-01-146-5801
Terminal Location:
Rear end
Mounting Method:
Terminal
Electrical Resistance Per Section:
100.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
360.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-100.0/+100.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

NSN 5905-01-217-8513

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Fiig: A002a0