## NSN 5905-01-218-2284

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-218-2284

Section Quantity:
2
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Shaft Diameter:
0.250 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.312 inches
Body Length:
1.025 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
240.0
Maximum Running Torque:
2.00 inch-ounces
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side two rows
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
15.000 kilohms all sections
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 all sections

## NSN 5905-01-218-2284

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



## Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:

-150.0 to 150.0 all sections

**Power Dissipation Rating Per Section In Watts:** 

1.0 free air all sections

**Resistance Tolerance Per Section In Percent:** 

-10.0 to 10.0 all sections

**Actuator Travel Control Feature:** 

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 all sections

**Terminal Type And Quantity:** 

6 wire loop

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

Fiig:

A002a0