NSN 5905-01-219-4839

Electrical Resistance:

Resistance Tolerance In Percent:

220.000 ohms

-1.000/+1.000

25.0

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-219-4839

Ambient Tempurature In Deg Celsius At Full Rated Power:

| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
|--|
| 275.0 |
| nclosure Method: |
| Encased |
| Ferminal Type: |
| Fab, solder lug |
| Reliability Indicator: |
| Established |
| Reliability Failure Rate Level In Percent: |
| 1.000 |
| Ferminal Length: |
| 0.266 inches |
| Body Length: |
| 0.600 inches |
| Body Width: |
| 0.334 inches |
| Body Height: |
| 0.320 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 0.444 inches |
| Power Dissipation Rating In Watts: |
| 5.000 free air |
| Ferminal Width: |
| 0.085 inches |
| Mounting Hole Size: |
| 0.050 inches |
| Style Designator: |
| Axial terminal (s) |
| Fest Data Document: |
| 81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| ormat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 31349-mil-r-39009/1 government specification |
| Shelf Life: |
| N/a |
| Jnit Of Measure: |
| - |
| |

NSN 5905-01-219-4839

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0