NSN 5905-01-219-5917

Inductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-219-5917
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-30.0/+30.0
Electrical Resistance:
552.000 ohms
Resistance Tolerance In Percent:
-1.000/+1.000
Ambient Tempurature In Deg Celsius At Full Rated Power:
25.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
275.0
Inclosure Method:
Encased
Terminal Type:
Tab, solder lug
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
Terminal Length:
Between 0.376 inches and 0.500 inches
Body Length:
Between 1.876 inches and 2.000 inches
Body Width:
Between 0.532 inches and 0.656 inches
Body Height:
Between 0.594 inches and 0.656 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
Between 0.834 inches and 0.854 inches
Power Dissipation Rating In Watts:
10.000 free air
Mounting Hole Size:
Between 0.120 inches and 0.130 inches
Style Designator:
Axial terminal (s)
Test Data Document:
81349-mil-r-39009 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-r-39009/1 government specification

--

N/a

Shelf Life:

Unit Of Measure:

NSN 5905-01-219-5917

Inductive Wire Wound Fixed Resistor - Page 2 of 2



_						
11	em)	 tor	172	+ 1	nn	

No

Fiig:

A001a0