Nonprecision Wire Wound Variable Resistor - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5905-01-219-5924



Section Quantity:

Body Style:

1

Rectangular w/mounting holes Reliability Indicator: Not established Terminal Length: 0.500 inches Mounting Hole Diameter: Between 0.071 inches and 0.078 inches Shaft Diameter: 0.078 inches Shaft Length: 0.036 inches Body Length: 0.500 inches Body Width: 0.192 inches

Body Height:

0.500 inches

Shaft Style:

Round, slotted

Actuator Type:

Single shaft

Maximum Starting Torque:

5.00 inch-ounces

Maximum Running Torque:

5.00 inch-ounces

Center To Center Distance Between Terminals:

0.200 inches

Lateral Distance Between Mounting Hole Centers:

Between 0.520 inches and 0.526 inches

Mounting Facility Quantity:

2

Terminal Location:

Lower adjacent side single row

Mounting Method:

Unthreaded hole

Electrical Resistance Per Section:

2.0 kilohms single section

Center To Center Distance Between Center Terminal And Outside Terminal:

0.100 inches



| Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: |
|---|
| 150.0 single section |
| Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius: |
| -50.0 to 50.0 single section |
| Power Dissipation Rating Per Section In Watts: |
| 1.0 free air single section |
| Resistance Tolerance Per Section In Percent: |
| -5.0 to 5.0 single section |
| Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: |
| 70.0 single section |
| Precious Material And Location: |
| Terminal surfaces gold |
| Precious Material: |
| Gold |
| Terminal Type And Quantity: |
| 3 pin |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| - |
| Demilitarization: |
| No |
| Fiig: |
| A002a0 |
| |