## NSN 5905-01-220-0713

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-220-0713 **Section Quantity:** 1 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.594 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.969 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve Switch Type: Rotary **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 6.00 inch-ounces **Maximum Running Torque:** 

Maximum Running Torque:
6.00 inch-ounces

Maximum Stop Torque:
64.00 inch-ounces

Switch Operating Position:
Start of rotation

Switch Contact Arrangement:

Double pole, double throw

## NSN 5905-01-220-0713

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



End Application:
6625-01-135-6685
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Right-left adjacent sides
Mounting Method:
Standard bushing
Features Provided:
Switch
Cubic Measure:
0.375 cubic inches
Electrical Resistance Per Section:
20.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
+0.0 to 5.0 -55 degrees celsius single section and +0.0 to 3.0 -25 degrees celsius single section and -1.5 to 1.5 0 degrees celsius single
section and -2.0 to 2.0 85 degrees celsius single section and -3.0 to 3.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
120.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:
A single section
Terminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

No

Demilitarization:

## NSN 5905-01-220-0713

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0