## NSN 5905-01-220-0714

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-220-0714

Section Quantity:
1
Body Style:
Rectangular bushing mounted
Reliability Indicator:
Not established
Overall Length:
1.594 inches
Shaft Diameter:
0.125 inches
Shaft Length:
0.625 inches
Mounting Bushing Length:
0.250 inches
Body Length:
0.969 inches
Body Width:
0.625 inches
Body Height:
0.625 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Sleeve
Switch Type:
Rotary
Switch Voltage Rating In Volts:
125.0
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
260.0
Maximum Starting Torque:
6.00 inch-ounces
Maximum Running Torque:
6.00 inch-ounces
Maximum Stop Torque:
64.00 inch-ounces
Switch Operating Position:
Start of rotation
Switch Contact Arrangement:

Double pole, double throw

## NSN 5905-01-220-0714

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



End Application:
6625-01-135-6685
Screw Thread Diameter:
0.250 inches
Screw Thread Series Designator:
Jnef
Screw Thready Qty Per Inch (tpi):
32.0
Ferminal Location:
Right-left adjacent sides
Mounting Method:
Standard bushing
Features Provided:
Switch
Cubic Measure:
0.379 cubic inches
Electrical Resistance Per Section:
50.000 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Resistance Tempurature Characteristic Range Per Section In Percent:
9.0/+0.0 -55 degrees celsius single section and -6.0/+0.0 -25 degrees celsius single section and -3.0/+0.0 0 degrees celsius single section
and +0.0/+6.5 85 degrees celsius single section and +0.0/+10.0 120 degrees celsius single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
20.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Switch Current Type And Rating In Amps:
2.000 ac
Standard Taper Curve Per Section:
A single section
Ferminal Type And Quantity:
7 tab, solder lug
Shelf Life:
N/a
Jnit Of Measure:
_

No

Demilitarization:

## NSN 5905-01-220-0714

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0