

View Online at <https://aerobasegroup.com/nsn/5905-01-220-8081>

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

Between 0.7495 inches and 0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.776 inches

Undercut Width:

0.0620 inches

Body Diameter:

0.875 inches

Shaft Diameter:

Between 0.1246 inches and 0.1249 inches

Shaft Length:

0.500 inches

Body Length:

1.282 inches

Mounting Lip Diameter:

0.8750 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round, slotted

Shaft Bearing Type:

Bearing

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

Between 3600.0 and 3610.0

Maximum Starting Torque:

0.40 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Maximum Stop Torque:

100.00 inch-ounces

Shaft End Play:

0.005 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

Pilot Diameter Runout:

0.002 inches

Shaft Radial Play:

0.002 inches

Fragility Factor:

Moderately rugged

Terminal Location:

Radially positioned over more than half the circumference

Mounting Method:

Clamp ring

Features Provided:

Humidity proof

Cubic Measure:

0.846 cubic inches

Rotary Actuator Travel In Angular Deg:

Between 3600.0 and 3610.0

Function Conformity Tolerance Per Section:

-0.25/+0.25 single section

Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:

125.0 single section

Power Dissipation Rating Per Section In Watts:

2.0 free air single section

Function Conformity Per Section:

Single section independent linearity

Fixed Tap Quantity Per Section:

1 single section

Actuator Travel Control Feature:

Stops

Function Characteristic Per Section:

Single section linear

Ambient Temperature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

4 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0