## NSN 5905-01-220-8081

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-220-8081

Section Quantity:
1
Body Style:
Cylindrical servo mounted
Reliability Indicator:
Not established
Pilot Diameter:
Between 0.7495 inches and 0.7500 inches
Pilot Length:
0.0620 inches
Undercut Diameter:
0.776 inches
Undercut Width:
0.0620 inches
Body Diameter:
0.875 inches
Shaft Diameter:
Between 0.1246 inches and 0.1249 inches
Shaft Length:
0.500 inches
Body Length:
1.282 inches
Mounting Lip Diameter:
0.8750 inches
Mounting Lip Depth:
0.0620 inches
Shaft Style:
Round, slotted
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Effective Electrical Rotation In Deg Angular Rotation:
Between 3600.0 and 3610.0
Maximum Starting Torque:
0.40 inch-ounces
Maximum Running Torque:
0.40 inch-ounces
Maximum Stop Torque:
100.00 inch-ounces
Shaft End Dlav:

0.005 inches

## NSN 5905-01-220-8081

Precision Wire Wound Variable Resistor - Page 2 of 3



Objets Demonstr
Shaft Runout:
0.002 inches
Lateral Runout:
0.002 inches
Pilot Diameter Runout:
0.002 inches
Shaft Radial Play:
0.002 inches
Fragility Factor:
Moderately rugged
Terminal Location:
Radially positioned over more than half the circumference
Mounting Method:
Clamp ring
Features Provided:
Humidity proof
Cubic Measure:
0.846 cubic inches
Rotary Actuator Travel In Angular Deg:
Between 3600.0 and 3610.0
Function Conformity Tolerance Per Section:
-0.25/+0.25 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.0 free air single section
Function Conformity Per Section:
Single section independent linearity
Fixed Tap Quantity Per Section:
1 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 single section
Terminal Type And Quantity:
4 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

## NSN 5905-01-220-8081

Precision Wire Wound Variable Resistor - Page 3 of 3



Fiig:

A002a0