Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-221-1651

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0/+20.0 first temp coefficient

## **Electrical Resistance:**

1.400 kilohms

# **Resistance Tolerance In Percent:**

-1.000/+1.000

## Ambient Tempurature In Deg Celsius At Full Rated Power:

## 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

## Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0 temp range of first temp coefficient

#### **Inclosure Method:**

Encapsulated

## **Terminal Type:**

Wire lead

## **Reactance Characteristic:**

Inductive

# Reliability Indicator:

Established

# **Reliability Failure Rate Level In Percent:**

0.001

#### **Terminal Length:**

1.500 inches

#### **Body Diameter:**

0.094 inches

## **Body Length:**

0.406 inches

# **Power Dissipation Rating In Watts:**

2.000 free air

## Cubic Measure (non-core):

0.003 cubic inches

## **Unpackaged Unit Weight:**

1.000 grams

## Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-prf-39007/8 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-prf-39007/8 government specification

# Shelf Life:

N/a

# NSN 5905-01-221-1651

Wire Wound Fixed Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0

Mil-std (military Standard):

Mil-prf-39007 spec.