NSN 5905-01-221-2302

Nonprecision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-221-2302 **Section Quantity:** 1 **Body Style:** Rectangular w/mounting holes **Reliability Indicator:** Not established **Terminal Length:** 0.500 inches **Mounting Hole Diameter:** 0.078 inches **Shaft Diameter:** 0.075 inches **Shaft Length:** 0.035 inches **Body Length:** 0.500 inches **Body Width:** 0.187 inches **Body Height:** 0.500 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 9000.0 **Maximum Starting Torque:** 5.00 inch-ounces **Maximum Running Torque:** 5.00 inch-ounces **Center To Center Distance Between Terminals: Lateral Distance Between Mounting Hole Centers:**

0.520 inches **Mounting Facility Quantity: Terminal Location:** Rear end **Mounting Method:** Terminal and unthreaded hole **Electrical Resistance Per Section:** 100.0 kilohms single section

NSN 5905-01-221-2302

A002a0

Nonprecision Wire Wound Variable Resistor - Page 2 of 2



Rotary Actuator Travel In Angular Deg:
9000.0
Center To Center Distance Between Center Terminal And Outside Terminal:
0.100 inches
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
150.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-70.0 to 70.0 single section
Power Dissipation Rating Per Section In Watts:
1.0 free air single section
Resistance Tolerance Per Section In Percent:
-5.0 to 5.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
50.0 single section
Terminal Type And Quantity:
3 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig: