## NSN 5905-01-221-5494

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-221-5494

| Tempurature Coefficie | ent Of Resistance | In Ppm Per | Deg Celsius: |
|-----------------------|-------------------|------------|--------------|
|                       |                   |            |              |

-50.0 to 50.0 first temp coefficient

**Electrical Resistance:** 

75.000 kilohms 2nd intermediate resistance value

**Resistance Tolerance In Percent:** 

-1.000 to 1.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 125.0 temp range of first temp coefficient

**Inclosure Method:** 

Hermetically sealed

**Terminal Quantity:** 

16

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.140 inches

**Body Length:** 

0.896 inches

**Body Width:** 

0.280 inches

**Body Height:** 

0.130 inches

**Schematic Diagram Designator:** 

Series network

**Power Dissipation Rating In Watts:** 

0.500 total network

Err Default:

Between 0.014 inches and 0.026 inches

Identical Value Resistor Quantity:

4 1st intermediate resistance value

**Special Features:** 

Burn in required

**Unpackaged Unit Weight:** 

2.0 grams

**Style Designator:** 

**Dual inline** 

## NSN 5905-01-221-5494

Film Fixed Resistor Network - Page 2 of 2



| Tact  | Data | Doci | ım   | nnt   |
|-------|------|------|------|-------|
| 1 521 | vala |      | uill | CIII. |

73030-5e4790/11 standard (includes industry or association standards, individual manufactureer standards, etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0