## NSN 5905-01-221-7983

Nonprecision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-221-7983 **Section Quantity:** 2 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 6.380 inches First Flat Length: 0.340 inches Flat Height: Between 0.205 inches and 0.235 inches **Body Diameter:** 4.000 inches **Shaft Diameter:** Between 0.245 inches and 0.255 inches **Shaft Length:** 0.880 inches **Mounting Bushing Length:** 0.380 inches **Body Length:** 5.500 inches **Overall Diameter:** 5.000 inches **Shaft Style:** Round, flatted **Shaft Bearing Type:** Sleeve Switch Type: Sensitive **Switch Voltage Rating In Volts:** 125.0 **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 305.0 **Maximum Starting Torque:** 96.00 inch-ounces **Maximum Running Torque:** 

96.00 inch-ounces

Maximum Stop Torque:

240.00 inch-ounces

## NSN 5905-01-221-7983

Nonprecision Wire Wound Variable Resistor - Page 2 of 3



Switch Operating Position:
End of rotation
Switch Contact Arrangement:
Single pole, double throw, three positions maintained
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Rear-bottom
Mounting Method:
Standard bushing
Features Provided:
Switch
Electrical Resistance Per Section:
30.0 ohms all sections
Rotary Actuator Travel In Angular Deg:
305.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
390.0 all sections
Power Dissipation Rating Per Section In Watts:
150.0 free air all sections
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-20.0 to 20.0 all sections
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 all sections
Switch Current Type And Rating In Amps:
15.000 ac
Standard Taper Curve Per Section:
A all sections
Special Features:
Item contains second switch with the same electrical ratings
Terminal Type And Quantity:
6 tab, solder lug and 6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:

-

## NSN 5905-01-221-7983

Nonprecision Wire Wound Variable Resistor - Page 3 of 3



_					
11	em)	 tor	172	n	

No

Fiig:

A002a0