

View Online at <https://aerobasegroup.com/nsn/5905-01-221-9816>

Section Quantity:

2

Body Style:

Cylindrical bushing mounted

Reliability Indicator:

Not established

Body Diameter:

0.920 inches

Shaft Diameter:

Between 0.264 inches and 0.266 inches

Shaft Length:

1.190 inches

Mounting Bushing Length:

0.375 inches

Body Length:

0.880 inches

Undercut Diameter:

Between 0.186 inches and 0.188 inches

Shaft Style:

Round, stepped

Shaft Bearing Type:

Sleeve

Actuator Type:

Dual concentric

Nonturn Device Location:

At 9 oclock

Fragility Factor:

Moderately rugged

Undercut Length:

0.440 inches

Screw Thread Diameter:

0.375 inches

Screw Thread Series Designator:

Unef

Screw Thread Qty Per Inch (tpi):

32.0

Terminal Location:

Radially positioned over less than half the circumference

Mounting Method:

Standard bushing

Features Provided:

Humidity proof

Electrical Resistance Per Section:

10.0 kilohms 1st section

Power Dissipation Rating Per Section In Watts:

0.5 free air 1st section

Resistance Tolerance Per Section In Percent:

-30.0 to 30.0 all sections

Actuator Travel Control Feature:

Stops

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A002a0