

View Online at <https://aerobasegroup.com/nsn/5905-01-221-9816>

**Section Quantity:**

2

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.920 inches

**Shaft Diameter:**

Between 0.264 inches and 0.266 inches

**Shaft Length:**

1.190 inches

**Mounting Bushing Length:**

0.375 inches

**Body Length:**

0.880 inches

**Undercut Diameter:**

Between 0.186 inches and 0.188 inches

**Shaft Style:**

Round, stepped

**Shaft Bearing Type:**

Sleeve

**Actuator Type:**

Dual concentric

**Nonturn Device Location:**

At 9 oclock

**Fragility Factor:**

Moderately rugged

**Undercut Length:**

0.440 inches

**Screw Thread Diameter:**

0.375 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Radially positioned over less than half the circumference

**Mounting Method:**

Standard bushing

**Features Provided:**

Humidity proof

**Electrical Resistance Per Section:**

10.0 kilohms 1st section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air 1st section

**Resistance Tolerance Per Section In Percent:**

-30.0 to 30.0 all sections

**Actuator Travel Control Feature:**

Stops

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0