Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-221-9869

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-50.0 to 50.0 first temp coefficient

#### **Electrical Resistance:**

105.263 kilohms highest resistance value

## **Resistance Tolerance In Percent:**

-1.000 to 1.000 each resistor

## Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 125.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 125.0 temp range of first temp coefficient

#### **Inclosure Method:**

Hermetically sealed

## Terminal Quantity:

16

#### **Terminal Type:**

Tab, solder lug

Reliability Indicator:

Not established

## **Terminal Length:**

0.140 inches

#### Body Length:

0.896 inches

#### Body Width:

0.280 inches

**Body Height:** 

0.130 inches

Schematic Diagram Designator:

Series network

#### **Power Dissipation Rating In Watts:**

0.500 total network

Err Default:

Between 0.014 inches and 0.026 inches

## Identical Value Resistor Quantity:

6 highest resistance value

## Special Features:

Burn in required

## Unpackaged Unit Weight:

2.0 grams

## Style Designator:

Dual inline

# NSN 5905-01-221-9869

Film Fixed Resistor Network - Page 2 of 2



#### **Test Data Document:**

73030-5e4790/11 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A001a0