## NSN 5905-01-221-9871

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-221-9871

Tempurature	Coefficient	Of Resistance	In Ppm	Per Deg	Celsius:
-------------	-------------	---------------	--------	---------	----------

-50.0 to 50.0 first temp coefficient

**Electrical Resistance:** 

95.000 kilohms intermediate resistance value

**Resistance Tolerance In Percent:** 

-1.000 to 1.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

125.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 125.0 temp range of first temp coefficient

**Inclosure Method:** 

Hermetically sealed

**Terminal Quantity:** 

14

**Terminal Type:** 

Tab, solder lug

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.140 inches

Body Length:

0.796 inches

**Body Width:** 

0.280 inches

**Body Height:** 

0.130 inches

**Schematic Diagram Designator:** 

Balanced ladder network

**Power Dissipation Rating In Watts:** 

0.500 total network

Err Default:

Between 0.014 inches and 0.026 inches

Identical Value Resistor Quantity:

4 highest resistance value

**Special Features:** 

Burn in required

**Unpackaged Unit Weight:** 

2.0 grams

**Style Designator:** 

**Dual inline** 

## NSN 5905-01-221-9871

Film Fixed Resistor Network - Page 2 of 2



## **Test Data Document:**

7303	0-5e4790/84 drawing	g (this is	s the basic g	overning dra	awing, suc	h as a contracto	or drawing,	original equ	uipment mar	nufacturer	drawing,
etc.;	excludes any specif	cation,	standard or	r other docur	ment that r	nay be referenc	ed in a bas	ic governing	drawing)		

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0