NSN 5905-01-221-9872

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-221-9872

	Tempurature	Coefficient Of	f Resistance Ir	Ppm P ا	'er Deg	Celsius:
--	-------------	----------------	-----------------	---------	---------	----------

-100.0 to 100.0 first temp coefficient

Electrical Resistance:

75.000 kilohms each resistor

Resistance Tolerance In Percent:

-1.000 to 1.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 125.0 temp range of first temp coefficient

Inclosure Method:

Encapsulated

Terminal Quantity:

16

Terminal Type:

Tab, solder lug

Reliability Indicator:

Not established

Terminal Length:

Between 0.125 inches and 0.150 inches

Body Length:

0.830 inches

Body Width:

Between 0.240 inches and 0.305 inches

Body Height:

0.135 inches

Schematic Diagram Designator:

Ladder network

Power Dissipation Rating In Watts:

1.600 total network

Err Default:

Between 0.015 inches and 0.022 inches

Identical Value Resistor Quantity:

15 each resistor

Unpackaged Unit Weight:

1.5 grams

Style Designator:

Dual inline

Test Data Document:

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5905-01-221-9872

Film Fixed Resistor Network - Page 2 of 2



Spec	ifica	tion	Data:
------	-------	------	-------

81349-mil-r-83401/2 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A001a0