

View Online at <https://aerobasegroup.com/nsn/5905-01-222-3579>

**Section Quantity:**

1

**Body Style:**

Cylindrical bushing mounted

**Reliability Indicator:**

Not established

**Body Diameter:**

0.516 inches

**Shaft Diameter:**

0.125 inches

**Shaft Length:**

1.000 inches

**Mounting Bushing Length:**

0.250 inches

**Body Length:**

0.500 inches

**Shaft Style:**

Round

**Actuator Type:**

Single shaft

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Radius:**

0.400 inches

**Screw Thread Diameter:**

0.250 inches

**Screw Thread Series Designator:**

Unef

**Screw Thready Qty Per Inch (tpi):**

32.0

**Terminal Location:**

Rear end

**Mounting Method:**

Standard bushing

**Electrical Resistance Per Section:**

2.500 kilohms single section

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

145.0 single section

**Power Dissipation Rating Per Section In Watts:**

1.0 free air single section

**Resistance Tolerance Per Section In Percent:**

-5.0/+5.0 single section

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

85.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0