## NSN 5905-01-222-4332

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-222-4332

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0 to 100.0 first temp coefficient

**Electrical Resistance:** 

5.110 kilohms each resistor

**Resistance Tolerance In Percent:** 

-1.000 to 1.000 each resistor

Ambient Tempurature In Deg Celsius At Full Rated Power:

70.0

Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

**Tempurature Range Of Tempurature Coefficient In Deg Celsius:** 

-55.0 to 125.0 temp range of first temp coefficient

**Inclosure Method:** 

Encapsulated

**Terminal Quantity:** 

1/

**Terminal Type:** 

Pin

**Reliability Indicator:** 

Not established

**Terminal Length:** 

0.350 inches

**Body Length:** 

0.305 inches

Body Width:

0.385 inches

**Body Height:** 

0.075 inches

**Schematic Diagram Designator:** 

Ladder network

**Power Dissipation Rating In Watts:** 

0.325 total network

**End Application:** 

B-1b

Identical Value Resistor Quantity:

13 each resistor

**Unpackaged Unit Weight:** 

0.050 grams

**Style Designator:** 

Flat pack

**Test Data Document:** 

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5905-01-222-4332

Film Fixed Resistor Network - Page 2 of 2



	Sı	peci	fica	tion	Data
--	----	------	------	------	------

81349-mil-r-83401/3 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A001a0