NSN 5905-01-222-8145

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-222-8145 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.203 inches **Shaft Diameter:** 0.250 inches **Shaft Length:** 1.250 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 1.047 inches **Body Width:** 0.625 inches **Body Height:** 0.725 inches **Undercut Diameter:** 0.094 inches **Shaft Style:** Round, stepped **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Undercut Length:** 0.625 inches **Screw Thread Diameter:** 0.375 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Lower adjacent side two rows **Mounting Method:**

Standard bushing

Rotary Actuator Travel In Angular Deg:

300.0

NSN 5905-01-222-8145

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 all sections
Actuator Travel Control Feature:
Stops
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A002a0