NSN 5905-01-222-8147

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-222-8147 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 1.214 inches **Body Diameter:** 0.500 inches **Shaft Diameter:** 0.200 inches **Shaft Length:** 0.490 inches **Mounting Bushing Length:** 0.250 inches **Body Length:** 0.453 inches **Shaft Style:** Round, slotted **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 260.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 48.00 inch-ounces **End Application:** 1425-01-166-2187 **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi):

32.0

Terminal Location:

Rear end

NSN 5905-01-222-8147

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Mounting Method:
Standard bushing
Features Provided:
Panel seal
Electrical Resistance Per Section:
10.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
295.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
175.0 single section
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-150.0 to 150.0 single section
Power Dissipation Rating Per Section In Watts:
0.5 free air single section
Resistance Tolerance Per Section In Percent:
-10.0 to 10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
125.0 single section
Standard Taper Curve Per Section:
A single section
Special Features:
Shaft is notched 0.300 inches from mounting surface; notch length 0.125 inches; v-type
Test Data Document:
18876-13153317 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A002a0