

View Online at https://aerobasegroup.com/nsn/5905-01-223-4020

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-20.0/+20.0

### **Electrical Resistance:**

2.610 kilohms

### **Resistance Tolerance In Percent:**

-0.100/+0.100

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 25.0

## Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

275.0

#### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+275.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Type:**

Wire lead

## \_ .. . .... . ..

Reliability Indicator:

#### Established

**Reliability Failure Rate Level In Percent:** 

0.001

## **Terminal Length:**

1.500 inches

#### Body Diameter:

0.312 inches

### Body Length:

0.875 inches

## **Power Dissipation Rating In Watts:**

7.000 free air

#### **End Application:**

Oq20 (v) 2/msm

#### Cubic Measure (non-core):

0.067 cubic inches

#### **Unpackaged Unit Weight:**

5.0 grams

#### Style Designator:

Axial terminal each end

## **Test Data Document:**

81349-mil-r-39007 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81349-mil-r-39007/10 government specification

# Shelf Life:

N/a

Inductive Wire Wound Fixed Resistor - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0