NSN 5905-01-224-1212

Film Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-224-1212 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -300.0 to 300.0 first temp coefficient |
| Electrical Resistance: |
| 5.100 kilohms each resistor |
| Resistance Tolerance In Percent: |
| -2.000 to 2.000 each resistor |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 150.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 150.0 temp range of first temp coefficient |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 16 |
| Terminal Type: |
| Tab, solder lug |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.140 inches |
| Body Length: |
| 0.850 inches |
| Body Width: |
| 0.300 inches |
| Body Height: |
| 0.102 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 1.750 total network |
| Err Default: |
| 0.019 inches |
| End Application: |
| Training dev |
| Identical Value Resistor Quantity: |
| 15 each resistor |
| Style Designator: |
| Dual inline |

N/a

Shelf Life:

NSN 5905-01-224-1212

Film Fixed Resistor Network - Page 2 of 2



| | 1 | :. | ~ | 84 | | | | |
|---|----|----|----|-----|----|----|------|---|
| ι | JN | IT | UΤ | IVI | ea | Sι | ire: | • |

--

Demilitarization:

No

Fiig:

A001a0