## NSN 5905-01-224-6519

Inductive Wire Wound Fixed Resistor - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5905-01-224-6519

| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:   |
|---|
| -10.0/+10.0   |
| Electrical Resistance:  |
| 12.000 kilohms  |
| Resistance Tolerance In Percent:  |
| -0.100/+0.100   |
| Ambient Tempurature In Deg Celsius At Full Rated Power:   |
| 125.0   |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:   |
| 175.0   |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius:  |
| -55.0/+175.0  |
| Inclosure Method:   |
| Encapsulated  |
| Terminal Type:  |
| Wire lead   |
| Reliability Indicator:  |
| Not established   |
| Terminal Length:  |
| 0.750 inches  |
| Body Diameter:  |
| 0.130 inches  |
| Body Length:  |
| 0.270 inches  |
| Power Dissipation Rating In Watts:  |
| 0.300 free air  |
| End Application:  |
| Triple torque   |
| Style Designator:   |
| Axial terminal each end   |
| Test Data Document:   |
| 89305-037924 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; |
| excludes any specification, standard or other document that may be referenced in a basic governing drawing)                             |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A001a0  |