Precision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-224-7977

Section Quantity:

1

Body Style:

Cylindrical servo mounted

Reliability Indicator:

Not established

Pilot Diameter:

0.7500 inches

Pilot Length:

0.0620 inches

Undercut Diameter:

0.781 inches

Undercut Width:

0.0570 inches

Body Diameter:

1.062 inches

Shaft Diameter:

0.125 inches

Shaft Length:

0.500 inches

Body Length:

0.810 inches

Mounting Lip Diameter:

Between 0.8650 inches and 0.8800 inches

Mounting Lip Depth:

0.0620 inches

Shaft Style:

Round

Actuator Type:

Single shaft

Effective Electrical Rotation In Deg Angular Rotation:

320.0

Maximum Starting Torque:

0.50 inch-ounces

Maximum Running Torque:

0.40 inch-ounces

Shaft End Play:

0.00500 inches

Shaft Runout:

0.002 inches

Lateral Runout:

0.002 inches

NSN 5905-01-224-7977

Precision Nonwire Wound Variable Resistor - Page 2 of 2



Pilot Diameter Runout: 0.00100 inches Shaft Radial Play: 0.001 inches **End Application:** B-1b aircraft **Terminal Location:** Radially positioned over less than half the circumference **Mounting Method:** Clamp ring **Electrical Resistance Per Section:** 1.000 kilohms single section **Rotary Actuator Travel In Angular Deg:** 360.0 Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power: 125.0 single section **Power Dissipation Rating Per Section In Watts:** 1.0 free air single section **Resistance Tolerance Per Section In Percent:** -10.0 to 10.0 single section **Actuator Travel Control Feature:** Continuous motion Ambient Tempurature In Deg Celsius Per Section At Full Rated Power: 70.0 single section **Test Data Document:** 81349-mil-r-39023 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 3 tab, solder lug **Specification Data:** 81349-mil-r-39023/1 government specification Shelf Life: N/a Unit Of Measure: **Demilitarization:** No Fiig: A002a0
