## NSN 5905-01-225-1261

Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-225-1261
Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-100.0 to 100.0 first temp coefficient
Electrical Resistance:
20.000 kilohms lowest resistance value
Resistance Tolerance In Percent:
-3.000 to 3.000 each resistor
Ambient Tempurature In Deg Celsius At Full Rated Power:
70.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
150.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 150.0 temp range of first temp coefficient
Inclosure Method:
Encapsulated
Terminal Quantity:
6
Terminal Type:
Pin
Reliability Indicator:
Not established
Terminal Length:
0.125 inches
Body Length:
0.590 inches
Body Width:
0.100 inches
Body Height:
0.200 inches
Schematic Diagram Designator:
Ladder network
Power Dissipation Rating In Watts:
0.125 total network
End Application:
Sincgars-v
Identical Value Resistor Quantity:
2 intermediate resistance value
Style Designator:
Single inline
Test Data Document:
80063-a3012857 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Shelf Life:

N/a

## NSN 5905-01-225-1261

Film Fixed Resistor Network - Page 2 of 2



		• •			
ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A001a0