NSN 5905-01-225-3376

Film Fixed Resistor Network - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5905-01-225-3376 |
|---|
| Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius: |
| -200.0 to 200.0 first temp coefficient |
| Electrical Resistance: |
| 10.000 kilohms each resistor |
| Resistance Tolerance In Percent: |
| -3.000 to 3.000 each resistor |
| Ambient Tempurature In Deg Celsius At Full Rated Power: |
| 70.0 |
| Ambient Tempurature In Deg Celsius At Zero Percent Rated Power: |
| 150.0 |
| Tempurature Range Of Tempurature Coefficient In Deg Celsius: |
| -55.0 to 150.0 temp range of first temp coefficient |
| Inclosure Method: |
| Encapsulated |
| Terminal Quantity: |
| 9 |
| Terminal Type: |
| Pin |
| Reliability Indicator: |
| Not established |
| Terminal Length: |
| 0.125 inches |
| Body Length: |
| 0.890 inches |
| Body Width: |
| 0.100 inches |
| Body Height: |
| 0.200 inches |
| Schematic Diagram Designator: |
| Ladder network |
| Power Dissipation Rating In Watts: |
| 0.050 total network |
| Identical Value Resistor Quantity: |
| 8 each resistor |
| Style Designator: |
| Single inline |
| Test Data Document: |
| 80063-a3012860 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, |
| etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

--

NSN 5905-01-225-3376

Film Fixed Resistor Network - Page 2 of 2



Demilitarization:

No

Fiig:

A001a0