Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-225-3378

# Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-200.0 to 200.0 first temp coefficient

# **Electrical Resistance:**

9.100 kilohms 1st intermediate resistance value

## **Resistance Tolerance In Percent:**

-3.000 to 3.000 each resistor

# Ambient Tempurature In Deg Celsius At Full Rated Power:

### 70.0

# Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

150.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0 to 150.0 temp range of first temp coefficient

#### **Inclosure Method:**

Encapsulated

### **Terminal Quantity:**

10

# Terminal Type:

Pin

### Reliability Indicator:

Not established

#### **Terminal Length:**

0.125 inches

### Body Length:

0.990 inches

#### Body Width:

0.100 inches

#### **Body Height:**

0.200 inches

Schematic Diagram Designator:

Balanced ladder network

#### **Power Dissipation Rating In Watts:**

0.125 total network

#### **End Application:**

Sincgars-v

#### **Identical Value Resistor Quantity:**

2 2nd intermediate resistance value

#### Style Designator:

Single inline

#### **Test Data Document:**

80063-a3012861 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Shelf Life:

Film Fixed Resistor Network - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0