Film Fixed Resistor Network - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-226-1938

## Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:

-300.0/+300.0

#### **Electrical Resistance:**

3.900 kilohms

**Resistance Tolerance In Percent:** 

-5.000/+5.000

### Ambient Tempurature In Deg Celsius At Full Rated Power:

#### 70.0

### Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:

125.0

### Tempurature Range Of Tempurature Coefficient In Deg Celsius:

-55.0/+125.0

#### **Inclosure Method:**

Encapsulated

#### **Terminal Quantity:**

8

# Terminal Type:

Pin

## Reliability Indicator:

Not established

### **Terminal Length:**

Between 0.125 inches and 0.150 inches

### **Body Length:**

0.783 inches

### **Body Width:**

0.074 inches

### **Body Height:**

0.187 inches

### Schematic Diagram Designator:

Ladder network

### **Power Dissipation Rating In Watts:**

0.840 total network

#### **End Application:**

Ele simulator

### Identical Value Resistor Quantity:

7 each resistor

## **Unpackaged Unit Weight:**

1.500 grams

#### Style Designator:

Single inline

#### **Test Data Document:**

81349-mil-r-83401 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Film Fixed Resistor Network - Page 2 of 2



**Specification Data:** 

81349-mil-r-83401/8 government specification

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A001a0