NSN 5905-01-226-3567

Precision Wire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-226-3567 **Section Quantity:** 1 **Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.2213 inches **Body Diameter:** 0.875 inches **Shaft Diameter:** 0.1248 inches **Shaft Length:** 0.750 inches **Mounting Bushing Length:** 0.313 inches **Body Length:** 1.440 inches **Overall Diameter:** 1.250 inches **Shaft Style:** Round **Shaft Bearing Type:** Sleeve **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 3600.0 **Maximum Starting Torque:** 0.50 inch-ounces **Maximum Running Torque:** 0.40 inch-ounces **Maximum Stop Torque:** 96.00 inch-ounces **Shaft End Play:** 0.004 inches **Shaft Runout:** 0.001 inches **Lateral Runout:**

Pilot Diameter Runout:

0.001 inches

0.002 inches

NSN 5905-01-226-3567

Mechanical Backlash In Deg Angular Rotation:

Shaft Radial Play: 0.002 inches

Fragility Factor:

1.0

Precision Wire Wound Variable Resistor - Page 2 of 3



Moderately rugged
End Application:
Drawer assembly
Screw Thread Diameter:
0.241 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Longitudinally positioned on the circumference
Mounting Method:
Standard bushing
Electrical Resistance Per Section:
5.0 kilohms single section
Rotary Actuator Travel In Angular Deg:
3600.0
Function Conformity Tolerance Per Section:
-0.20 to 0.20 single section
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
2.75 free air single section
Function Conformity Per Section:
Single section independent linearity
Resistance Tolerance Per Section In Percent:
-3.0 to 3.0 single section
Actuator Travel Control Feature:
Stops
Function Characteristic Per Section:
Single section linear
Tempurature Coefficient Of Resistance Wire Per Section In Ppm Per Deg Celsius:
-10.0 to 10.0 single section
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
40.0 single section
Terminal Type And Quantity:
3 turret
Shelf Life:
N/a

NSN 5905-01-226-3567

Precision Wire Wound Variable Resistor - Page 3 of 3



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A002a0