## NSN 5905-01-227-9813

Noninductive Wire Wound Fixed Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-227-9813

Tempurature Coefficient Of Resistance In Ppm Per Deg Celsius:
-90.0 to 90.0
Electrical Resistance:
0.121 ohms
Resistance Tolerance In Percent:
-0.250 to 0.250
Ambient Tempurature In Deg Celsius At Full Rated Power:
125.0
Ambient Tempurature In Deg Celsius At Zero Percent Rated Power:
145.0
Tempurature Range Of Tempurature Coefficient In Deg Celsius:
-55.0 to 145.0
Inclosure Method:
Encapsulated
Terminal Type:
Wire lead
Mil-std-1276 Wire Lead Type Designator:
С
Reliability Indicator:
Established
Reliability Failure Rate Level In Percent:
0.100
0.100 Terminal Length:
Terminal Length:
Terminal Length: 1.500 inches
Terminal Length: 1.500 inches Body Diameter:
Terminal Length: 1.500 inches  Body Diameter: 0.375 inches
Terminal Length: 1.500 inches  Body Diameter: 0.375 inches  Body Length:
Terminal Length: 1.500 inches  Body Diameter: 0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc  Unpackaged Unit Weight:
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc  Unpackaged Unit Weight:  6.0 grams
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc  Unpackaged Unit Weight:  6.0 grams  Style Designator:
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc  Unpackaged Unit Weight:  6.0 grams  Style Designator:  Axial terminal each end
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc  Unpackaged Unit Weight:  6.0 grams  Style Designator:  Axial terminal each end  Shelf Life:
Terminal Length:  1.500 inches  Body Diameter:  0.375 inches  Body Length:  Between 0.680 inches and 1.020 inches  Power Dissipation Rating In Watts:  0.500 free air  End Application:  Am-6624a/msc  Unpackaged Unit Weight:  6.0 grams  Style Designator:  Axial terminal each end  Shelf Life:  N/a

No

## NSN 5905-01-227-9813

Noninductive Wire Wound Fixed Resistor - Page 2 of 2



Fiig:

A001a0