NSN 5905-01-228-3020

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 3



View Online at https://aerobasegroup.com/nsn/5905-01-228-3020 **Section Quantity:** 2 **Body Style:** Rectangular bushing mounted **Reliability Indicator:** Not established **Overall Length:** 2.500 inches **Overall Height:** 0.835 inches **Overall Width:** 0.625 inches **Shaft Diameter:** 0.220 inches **Shaft Length:** 1.125 inches **Mounting Bushing Length:** 0.375 inches **Body Length:** 1.250 inches **Body Width:** 0.625 inches **Body Height:** 0.625 inches **Undercut Diameter:** 0.097 inches **Shaft Style:** Round, stepped **Shaft Bearing Type:** Sleeve **Actuator Type:** Dual concentric **Effective Electrical Rotation In Deg Angular Rotation:** 240.0 **Maximum Starting Torque:** 2.00 inch-ounces **Maximum Running Torque:**

2.00 inch-ouncesMaximum Stop Torque:64.00 inch-ounces

Nonturn Device Location:

At 9 oclock

NSN 5905-01-228-3020

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 3



Nonturn Device Radius:
0.305 inches
Fragility Factor:
Moderately rugged
End Application:
A/f-18-dcn
Undercut Length:
0.375 inches
Screw Thread Diameter:
0.375 inches
Screw Thread Series Designator:
Unef
Screw Thready Qty Per Inch (tpi):
32.0
Terminal Location:
Lower adjacent side single row
Mounting Method:
Standard bushing
Cubic Measure:
1.305 cubic inches
Electrical Resistance Per Section:
200.0 ohms 1st section and 100.0 ohms 2nd section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 all sections
Tempurature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:
-1000.0 to 1000.0 1st section
Power Dissipation Rating Per Section In Watts:
0.5 free air 1st section and 1.0 free air 2nd section
Resistance Tolerance Per Section In Percent:
-20.0 to 20.0 1st section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
70.0 all sections
Standard Taper Curve Per Section:
A all sections
Terminal Type And Quantity:
6 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

-

NSN 5905-01-228-3020

Nonprecision Nonwire Wound Variable Resistor - Page 3 of 3



em			

No

Fiig:

A002a0