NSN 5905-01-228-6793

Precision Wire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-228-6793

Section Quantity:
1
Body Style:
Cylindrical bushing mounted
Reliability Indicator:
Not established
Body Diameter:
2.000 inches
Shaft Diameter:
0.2497 inches
Shaft Length:
0.875 inches
Mounting Bushing Length:
0.375 inches
Body Length:
0.905 inches
Shaft Style:
Round
Shaft Bearing Type:
Bearing
Actuator Type:
Single shaft
Maximum Starting Torque:
1.50 inch-ounces
Maximum Running Torque:
1.10 inch-ounces
Shaft End Play:
0.00500 inches
Terminal Location:
Radially positioned over less than half the circumference
Mounting Method:
Tab
Features Provided:
Shaft locking device
Electrical Resistance Per Section:
80.000 kilohms single section
Rotary Actuator Travel In Angular Deg:
356.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
125.0 single section
Power Dissipation Rating Per Section In Watts:
3.5 free air single section

NSN 5905-01-228-6793

Precision Wire Wound Variable Resistor - Page 2 of 2



Resistance	Tolerance	Per	Section	ln	Percent:
------------	-----------	-----	---------	----	----------

-5.0 to 5.0 single section

Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:

70.0 single section

Terminal Type And Quantity:

3 turret

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A002a0