

View Online at <https://aerobasegroup.com/nsn/5905-01-228-8677>

**Section Quantity:**

1

**Body Style:**

Rectangular

**Reliability Indicator:**

Not established

**Overall Length:**

0.785 inches

**Terminal Length:**

0.140 inches

**Overall Height:**

0.325 inches

**Overall Width:**

0.080 inches

**Body Length:**

0.785 inches

**Body Width:**

0.080 inches

**Body Height:**

0.185 inches

**Shaft Bearing Type:**

Bearing

**Actuator Type:**

Flush drive with slot-hole

**Effective Electrical Rotation In Deg Angular Rotation:**

5400.0

**Maximum Starting Torque:**

5.00 inch-ounces

**Maximum Running Torque:**

5.00 inch-ounces

**Center To Center Distance Between Terminals:**

0.700 inches

**Fragility Factor:**

Moderately rugged

**End Application:**

Gyro test con

**Terminal Location:**

Lower adjacent side single row

**Mounting Method:**

Terminal

**Cubic Measure:**

0.020 cubic inches

**Electrical Resistance Per Section:**

1.000 kilohms single section

**Rotary Actuator Travel In Angular Deg:**

5400.0

**Center To Center Distance Between Center Terminal And Outside Terminal:**

0.600 inches

**Ambient Temperature In Deg Celsius Per Section At Zero Percent Rated Power:**

125.0 single section

**Temperature Coefficient Of Resistance Per Section In Ppm Per Deg Celsius:**

-100.0 to 100.0 single section

**Power Dissipation Rating Per Section In Watts:**

0.5 free air single section

**Resistance Tolerance Per Section In Percent:**

-10.0 to 10.0 single section

**Actuator Travel Control Feature:**

Stops

**Ambient Temperature In Deg Celsius Per Section At Full Rated Power:**

25.0 single section

**Standard Taper Curve Per Section:**

A single section

**Terminal Type And Quantity:**

3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A002a0