## NSN 5905-01-229-1380

Nonprecision Nonwire Wound Variable Resistor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5905-01-229-1380 **Section Quantity: Body Style:** Cylindrical bushing mounted **Reliability Indicator:** Not established **Terminal Length:** 0.250 inches **Body Diameter:** 0.525 inches **Shaft Diameter:** 0.125 inches **Shaft Length:** 0.625 inches **Mounting Bushing Length:** Between 0.219 inches and 0.297 inches **Body Length:** 0.656 inches **Shaft Style:** Round, slotted **Actuator Type:** Single shaft **Effective Electrical Rotation In Deg Angular Rotation:** 300.0 **Maximum Starting Torque:** 3.00 inch-ounces **Maximum Running Torque:** 3.00 inch-ounces **Maximum Stop Torque:** 80.00 inch-ounces **End Application:** Test set elec **Screw Thread Diameter:** 0.250 inches **Screw Thread Series Designator:** Unef Screw Thready Qty Per Inch (tpi): 32.0 **Terminal Location:** Rear end

**Mounting Method:** 

Standard bushing

## NSN 5905-01-229-1380

A002a0

Nonprecision Nonwire Wound Variable Resistor - Page 2 of 2



Electrical Resistance Per Section:
100.000 ohms single section
Rotary Actuator Travel In Angular Deg:
300.0
Ambient Tempurature In Deg Celsius Per Section At Zero Percent Rated Power:
340.0 single section
Power Dissipation Rating Per Section In Watts:
5.0 heat sink single section
Resistance Tolerance Per Section In Percent:
-10.0/+10.0 single section
Actuator Travel Control Feature:
Stops
Ambient Tempurature In Deg Celsius Per Section At Full Rated Power:
25.0 single section
Standard Taper Curve Per Section:
A single section
Test Data Document:
81349-mil-r-22 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 tab, solder lug
Specification Data:
81349-mil-r-22/15 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig: